

SALT Functions: Syntax

Boot function syntax:

```
for .dyapp files: □SE.SALT.Boot '{path/filename} [.dyapp]'
```

```
for .dyalog files: □SE.SALT.Boot '{path/filename}{.dyalog} [-xload]
                    ['argument']
```

Clean function syntax:

```
□SE.SALT.Clean '[objects] [-deletefiles]'
```

Compare function syntax:

```
□SE.SALT.Compare '{path/filename} [-version{=vers}] [-permanent]
                  [-using{=program}] [-window{=lines}] [-trim] [-symbols{=symbols}]'
```

List function syntax:

```
□SE.SALT.List '[directory|.dyalog file] [-folders] [-versions]
               [-extension{=ext}] [-full{=value}] [-recursive] [-raw] [-type]'
```

Load function syntax:

```
□SE.SALT.Load '{path/name} [-target{=namespace}] [-noname]
               [-disperse{=objects}] [-nolink] [-source{=no}] [-version{=vers}]
               [-protect]'
```

New function syntax:

```
□SE.SALT.New '{path/filename} [.ext] [-version{=vers}]
              ['arg|(args)']
```

RemoveVersions function syntax:

```
□SE.SALT.RemoveVersions '{path/filename} [.ext] [-collapse]
                         [-version{=vers}] [-all] [-noprompt]'
```

Save function syntax:

```
□SE.SALT.Save '{objectname} [path/filename] [.extension] [-mkdir]
               [-version{=vers}] [-convert] [-banner{=top}] [-noprompt]
               [-format{=APL|XML}]'
```

Settings function syntax:

```
□SE.SALT.Settings '[parameter] [value] [-reset] [-permanent]'
```

Snap function syntax:

```
□SE.SALT.Snap '[fullpath] [-class{=nameclass}] [-convert]
                [-banner{=top}] [-fileprefix{=prefix}] [-mkdir] [-nosource]
                [-loadfn{=[+]path}] [-show{=details}] [-patterns{=string}]
                [-noprompt] [-version{=vers}] [-format{=APL|XML}] [-ΔΔ{=chars}]'
```