

# SALT Functions: Syntax

Boot function syntax:

```
□SE.SALT.Boot '{path/filename} [.dyapp]'
```

```
□SE.SALT.Boot '{path/filename}{.dyalog} [-xload]
  ['argument']
```

Compare function syntax:

```
□SE.SALT.Compare '{path/filename} [-version{=vers}] [-permanent]
  [-using{=program}] [-window{=lines}] [-trim] [-symbols{=symbols}]'
```

List function syntax:

```
□SE.SALT.List '[directory|.dyalog file] [-folders] [-versions]
  [-extension[=ext]] [-full[=value]] [-recursive] [-raw] [-type]'
```

Load function syntax:

```
□SE.SALT.Load '{path/name} [-target{=namespace}] [-noname]
  [-disperse[=objects]|-nolink] [-source[=no]] [-version{=vers}]
  [-protect]'
```

New function syntax:

```
□SE.SALT.New '{path/filename} [.ext] [-version{=vers}]
  ['arg|(args)']
```

Open function syntax:

```
□SE.SALT.Open '{path}[filename] [-using{=program}] [-permanent]'
```

RemoveVersions function syntax:

```
□SE.SALT.RemoveVersions '{path/filename} [.ext] [-collapse]
  [-version{=vers}|-all] [-noprompt]'
```

Save function syntax:

```
□SE.SALT.Save '{objectname} [path/filename] [.extension] [-mkdir]
  [-version[=vers]] [-convert] [-banner{=top}] [-noprompt]
  [-format[=APL|XML]]'
```

Settings function syntax:

```
□SE.SALT.Settings '[parameter] [value] [-reset] [-permanent]'
```

Snap function syntax:

```
□SE.SALT.Snap '[fullpath] [-class{=nameclass}] [-convert]
  [-banner{=top}] [-fileprefix{=prefix}] [-mkdir] [-loadfn[=path]]
  [-nosource] [-show[=details]] [-patterns{=string}] [-noprompt]
  [-version[=vers]] [-format[=APL|XML]] [-ΔΔ{=chars}]'
```