

User Commands Release Notes

User Commands Version 2.7

Dyalog Limited

Minchens Court, Minchens Lane
Bramley, Hampshire
RG26 5BH
United Kingdom

tel: +44 1256 830030
fax: +44 1256 830031
email: support@dyalog.com
<http://www.dyalog.com>

Dyalog is a trademark of Dyalog Limited
Copyright © 1982-2025



*Dyalog is a trademark of Dyalog Limited
Copyright © 1982 - 2025 by Dyalog Limited.
All rights reserved.*

Version 2.7

Revision: 20250812_270

Dyalog Limited makes no representations or warranties with respect to the contents hereof and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose. Dyalog Limited reserves the right to revise this publication without notification.

Raspberry Pi is a trademark of the Raspberry Pi Foundation.

Oracle®, MySQL, and Java™ are registered trademarks of Oracle and/or its affiliates. JavaScript™ is a trademark of Oracle Corporation.

Unicode is a registered trademarks of Unicode, Inc. in the United States and other countries.

UNIX® is a registered trademark in the U.S. and other countries, licensed exclusively through X/Open Company Limited.

Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

Windows® is a registered trademark of Microsoft Corporation in the U.S. and other countries.

macOS® and OS X® (operating system software) are registered trademarks of Apple Inc. in the U.S. and other countries

All other trademarks and copyrights are acknowledged.

Contents

1	ABOUT THIS DOCUMENT	1
1.1	Compatibility with Dyalog Versions	1
2	FUNCTIONAL CHANGES	2
2.1	Changes – Groups	2
2.1.1	New Groups	2
2.2	Changes – User Commands.....	2
2.2.1	New User Commands	2
2.2.2	Changed User Commands.....	3

1 About This Document

This document describes the changes and new features in user commands version 2.7 (released with the first release of Dyalog v20.0) compared with user commands v 2.6 (released with the first release of Dyalog version 19.0).

1.1 Compatibility with Dyalog Versions

The user command framework v2.7 is compatible with Dyalog v20.0 only.

2 Functional Changes

This chapter details the changes made to user commands for v2.7.

2.1 Changes – Groups

2.1.1 New Groups

One new group has been added. This is detailed in Table 1.

Table 1. New Groups

Group Name	Description
APLAN	User commands that determine use of APL array notation.
IT	User commands that open additional windows when tracing inline.

2.2 Changes – User Commands

2.2.1 New User Commands

Some new user commands have been added. These are detailed in Table 2.

Table 2. New User Commands

Group	User Command	Description
APLAN	Editor	Toggle use of APL array notation for editing variables.
APLAN	Output	Toggle use of APL array notation for session output.
IT	Axis	Open the Axis Specification window for inline tracing.
IT	Function	Open the Current Function window for inline tracing.
IT	Left	Open the Left Argument window for inline tracing.
IT	PAxis	Open the Previous Axis window for inline tracing.
IT	PFunction	Open the Previous Function window for inline tracing.
IT	PLeft	Open the Previous Left window for inline tracing.
IT	PRight	Open the Previous Right window for inline tracing.
IT	Result	Open the Previous Result window for inline tracing.
IT	Right	Open the Right Argument window for inline tracing.

2.2.2 Changed User Commands

Some user commands have been changed. These are detailed in Table 3.

Table 3. Changed User Commands

Group	User Command	Change
ARRAY	<code>Edit</code>	Prior to this release, the <code>]Edit</code> user command opened David Liebtage's Array Editor. It now opens the default editor with array notation enabled (if possible). Note: This user command is now deprecated and will be removed in a future release. To open the default editor with array notation enabled (if possible) use <code>)ED ⋄</code> or <code>'⋄'ED</code>.